

## LIGHTS & LIGHTING / LED

### LED

#### (ARRI)

##### ARRI L7-C LE2 LED Fresnel

Features: 25% increase boost in power, beam angle 12-50°, 2800-10K, and low electrical draw at 160W.

*Includes: (1) barndoor and (1) scrim set.*

##### ARRI SkyPanel S30-C LED Softlight

Smaller, more portable version than the S60, ideal for on-the-go applications. Outputs the equivalent of a 1000W tungsten soft light while drawing a maximum of only 240W.

*Includes: (1) ARRI SkyPanel Intensifier S30, (1) light diffusion panel, (1) medium diffusion panel, (1) heavy diffusion panel, (1) rail mount adapter, (1) AC/DC power pcable, and (1) power supply.*

##### SKYPANEL ACCESSORIES:

ARRI Chimera Shallow Lightbank – Medium (SkyPanel S30)  
ARRI SkyPanel Remote

##### ARRI SkyPanel S60-C LED Softlight

Outputs the equivalent of a 2000W tungsten soft light while drawing a maximum of only 450W.

*Includes: (1) ARRI SkyPanel Intensifier S60, (1) light diffusion panel, (1) medium diffusion panel, (1) heavy diffusion panel, (1) rail mount adapter, (1) AC/DC power cable, and (1) power supply.*

##### SKYPANEL ACCESSORIES:

ARRI Chimera Shallow Lightbank – Medium (SkyPanel S60)  
ARRI SkyPanel Honeycomb 30° S60  
ARRI SkyPanel Honeycomb 60° S60  
ARRI SkyPanel Remote

#### (ikan)

##### ikan ID500 12"x6" LED Light (5600K)

Features wireless remote with dimming capabilities and AC/DC 12-24V pro battery options.

*Includes: (1) wireless remote and (1) set of barndoors.*

##### ikan ID1000 12"x12" LED Light (5600K)

Features: wireless remote with dimming capabilities, switchable banks, and AC/DC 12-24V pro battery options.

*Includes: (1) wireless remote and (1) set of barndoors.*

#### (Litegear)

##### LiteGear LiteRibbon Pro LED Kit – V1 HYBRID (3200K-6000K)

*Includes: (1) pelican case; (1) set of assorted flexible (cuttable) adhesive-backed LiteRibbon(R), LiteRibbon(R) Chroma, LiteStix(TM) Pro, LitePower(TM); and (1) DTAP batter adapter.*

##### LiteGear S2 Litemat 1 Kit – Hybrid

Ultra lightweight, soft color-correct hybrid (bi-color) for daylight/tungsten with a 95 CRI, and a widened kelvin temperature range. Size: 9.5"x19".

#### (Litegear) Cont. –

##### LiteGear S2 Litemat 2L Kit – Hybrid

Ultra lightweight, soft color-correct hybrid (bi-color) for daylight/tungsten with a 95+ CRI, and a widened kelvin temperature range (without an increase in power draw). Size: 9.5"x19".

##### LiteGear S2 Litemat 4 Kit – Hybrid

Ultra lightweight, soft color-correct hybrid (bi-color) for daylight/tungsten with a 98 CRI. Features flicker-free dimming and variable color temperature control. Size: 40"x21".

#### (Litepanels)

##### Litepanels 1x1 Bi-Color LED Flood

Features: variable 3200-5600K color temperature, 50° beam angle, equivalent output of a 200W HMI light (heat and flicker free), and dimmable from 100 to 0%.

##### Litepanels 1x1 Daylight LED Flood (5600K)

*Includes: (1) 6-piece bi-color gel set and (1) gel bag.*

##### Litepanels Astra 1x1 Bi-Color LED Panel

Features: maximum power draw of 110W, flicker-free, and color range of 3200-5600K.

##### Litepanels Astra 6X Bi-Color LED Panel

Features: variable tungsten to daylight balance, maximum power draw of 105W, beam angle of 46°, and color range of 3200-5600K.

#### (Kino Flo)

##### Kino Flo Celeb 200 DMX LED

Features: flicker-free, color temperature of 2700-5500K, LED equivalent to 750W tungsten, and dimming/programmable presets from 2700K to 5500K.

##### Kino Flo Celeb 401 DMX LED

Features: LED equivalent to 2000W tungsten soft light, color temperature of 2700-6500K, and flicker-free with silent operation.

#### (Quasar Science)

##### Quasar Science Q-LED X Crossfade LED Lamp – 2'

Features: 25W tubes (producing 90 lumens per watt), dimmable, flicker free, 95+ CRI, aluminum built frame, and tungsten color temperature from 2000K to daylight 6000K.

##### Quasar Science Q-LED X Crossfade LED Lamp – 4'

Features: 50W tubes (producing 90 lumens per watt), dimmable, flicker free, 95+ CRI, aluminum built frame, and tungsten color temperature from 2000K to daylight 6000K.