

LIGHTS & LIGHTING / LED

LED

(Aladdin)

Aladdin A-LITE Bi-Color Dimmable LED Light

Portable, high-end variable bi-color on-board LED light with integrated lithium-ion battery (up to 1 hour and 20 minutes runtime), completely dimmable from 5–100%; generates a color-temperature range from tungsten (2900°K) to daylight (6300°K) and every point in-between.

Includes: (1) Aladdin A-LITE Bi-Color Dimmable Light Fixture, (2) Aladdin A-LITE Li-Ion Batteries, (1) Aladdin 3/8" to 1/4"-20 Adapter, and (1) Aladdin A-LITE External Interchangeable Battery Charger.

(ARRI)

ARRI L7-C LE2 LED Fresnel

Features: 25% increase boost in power, beam angle 12-50°, 2800-10K, and low electrical draw at 160W.

Includes: (1) barndoor and (1) scrim set.

ARRI Orbiter LED Open Face Light with Lens (Blue/Silver)

Kit Features: tunable color light system with six-color light engine including red, green, blue, amber, cyan, and lime LEDs, high CRI of 98, 2000-20K, and full continuous dimming 0 to 100%.

Includes: set of (3) lenses (15°, 30°, and 60°); (1) manual yoke; controller; (1) ARRI Chimera Lightbank M for Orbiter LED Light; (2) barndoors and (1) scrim set.

ARRI SkyPanel S30-C LED Softlight

Smaller, more portable version than the S60, ideal for on-the-go applications. Outputs the equivalent of a 1000W tungsten soft light while drawing a maximum of only 240W.

Includes: (1) ARRI SkyPanel Intensifier S30, (1) light diffusion panel, (1) medium diffusion panel, (1) heavy diffusion panel, (1) rail mount adapter, (1) AC/DC power pcable, and (1) power supply.

SKYPANEL ACCESSORIES:

ARRI Chimera Shallow Lightbank – Medium (SkyPanel S30)
ARRI SkyPanel Remote

ARRI SkyPanel S60-C LED Softlight

High-powered, fully tuneable LED for fine adjustments. Outputs the equivalent of a 2000W tungsten soft light while drawing a maximum of only 450W.

Includes: (1) ARRI SkyPanel Intensifier S60, (1) light diffusion panel, (1) medium diffusion panel, (1) heavy diffusion panel, (1) rail mount adapter, (1) AC/DC power cable, and (1) power supply.

SKYPANEL ACCESSORIES:

ARRI Chimera Shallow Lightbank – Medium (SkyPanel S60)
ARRI DoPchoice SNAPBAG® Chimera Octa 5 For SkyPanel S60
ARRI DoPchoice SNAPBAG® Softbox for SkyPanel S60
ARRI DoPchoice SNAPGRID® 40° for SnapBag S60
ARRI SkyPanel Honeycomb 30° S60
ARRI SkyPanel Honeycomb 60° S60
ARRI SkyPanel Intensifier S60

(ARRI) Cont. –

ARRI SkyPanel S60-C LED Softlight (Cont.)

SKYPANEL ACCESSORIES: (Cont.)

ARRI SkyPanel Remote

(Astera LED)

Astera Helios FP2 Wireless LED Light Tube Set (x8)

System of eight Helios FP2 36W power wireless, 8 pixel segment LED batons for variety of lighting applications.

Includes: (8) FP2 Helios Tubes, (1) FP2 Charging Case, (1) FP2 Power Box, (1) FP2 Charger, (1) Smart Pad w/Astera App, (1) ART7 AsteraBox CRMX, (1) ART7 DMX Cable Adapter, (8) Stands, (16) Holders, (16) Eyebolts, (16) holder cotter pins, and (16) ½-20 to 3/8-16 Threaded Manfrotto Stud (Spigot).

HELIOS ACCESSORIES:

Astera Helios FP2 Handle with 5/8" Baby Pin
SNAPBAG® (Helios FP2 Tube)
SNAPGRID® – 40° (Helios FP2 Tube)

Astera LED AX1 Wireless PixelTube Kit w/Charging Case

System of eight wireless, pixel controllable LED RGBW batons for variety of lighting applications.

Includes: (8) AX1 PixelTubes (3 ½"), (1) AX1 Charging Case, (8) charging cables, (8) AX1 Stands, (16) AX1 Holders, (16) AX1 Eyebolts, (16) holder cotter pins, (16) ½-20 to 3/8-16 Threaded Manfrotto Stud (Spigot), (1) transmitter case, (1) transmitter box, (1) Infra Red Remote Control, (1) micro USB cable, (1) USB adapter, (1) DMX adapter cable, and (1) AX1 single charging cable.

Astera Titan FP1 Wireless LED Light Kit w/Charging Case

System of eight Titan FP1 72W power wireless, 16 pixel segment LED batons for variety of lighting applications.

Includes: (8) FP1 Titan Tubes, (1) FP1 Charging Case, (1) FP1 Power Box, (1) FP1 Charger, (1) Smart Pad w/Astera App, (1) ART7 AsteraBox CRMX, (1) ART7 DMX Cable Adapter, (8) Stands, (16) Holders, (16) Eyebolts, (16) holder cotter pins, and (16) ½-20 to 3/8-16 Threaded Manfrotto Stud (Spigot).

(ETC Source Four)

ETC Source Four LED Series 2 Lustr w/Shutter Barrel

LED fixture incorporates the seven color x7 system with an array of 60 Luxeon Rebel LED emitters to provide a range of colors (red, green, amber, cyan, blue, indigo, and lime). Features: CRI >90 at 5600K, 15-bit virtual dimming, DMX512 in/out with 5-pin XLR ports, quiet fan cooling, with an LED lifetime of 20,000 hrs.

Includes: (1) gel frame and (1) drop-in iris.

ACCESSORIES:

ETC Source Four Drop-In Iris
ETC Source Four Enhanced Definition Lens Tube (19°)
ETC Source Four Enhanced Definition Lens Tube (26°)
ETC Source Four Enhanced Definition Lens Tube (36°)
ETC Source Four Enhanced Definition Lens Tube (50°)
ETC Source Four Pattern Holder (B Size)

LED - CONT.

(Kino Flo)

Kino Flo Celeb 200 DMX LED

Features: flicker-free, color temperature of 2700-5500K, LED equivalent to 750W tungsten, and dimming/programmable presets from 2700K to 5500K.

Kino Flo Celeb 401 DMX LED

Features: LED equivalent to 2000W tungsten soft light, color temperature of 2700-6500K, and flicker-free with silent operation.

(Lighting Control Products)

Lighting Control Products 2' 4Bank Housing for Astera Titans

2' 4Bank housing designed specifically for Astera Helios LED tubes (tubes not included).

Lighting Control Products 4' 4Bank Housing for Astera Titans

4' 4Bank housing designed specifically for Astera AX1 & Titan LED tubes (tubes not included).

Lighting Control Products 4' 4Bank Housing w/Dimmer (Longboard)

4' 4Bank housing designed specifically for Quasar Science LED lamps (lamps not included), a modern replacement for old-school Kinos.

Includes: (1) dimmer.

(LiteGear)

LiteGear LiteMat Plus 2 Kit with LiteDimmer Plus Duo

Ultra lightweight soft light fixture with two 'tiled' light engines and a color temperature range from 2600K to 6000K. Features flicker-free dimmer and variable color temperature control. Size: 21"x21"x9".

LiteGear LiteMat Plus 4 Kit with LiteDimmer Plus

Ultra lightweight, soft color-correct hybrid (bi-color) with a 95+ CRI and a color temperature range from 2600K to 6200K. Features flicker-free dimmer and variable color temperature control. Size: 21"x40"x9".

LiteGear LiteRibbon Pro LED Kit – V1 HYBRID (3200K-6000K)

Includes: (1) pelican case; (1) set of assorted flexible (cuttable) adhesive-backed LiteRibbon(R), LiteRibbon(R) Chroma, LiteStix(TM) Pro, LitePower(TM); and (1) DTAP battery adapter.

LiteGear S2 Litemat 1 Kit – Hybrid

Ultra lightweight, soft color-correct hybrid (bi-color) for daylight/tungsten with a 95+ CRI, and a widened kelvin temperature range. Size: 9.5"x19".

LiteGear S2 Litemat 2L Kit – Hybrid

Ultra lightweight, soft color-correct hybrid (bi-color) for daylight/tungsten with a 95+ CRI, and a widened kelvin temperature range (without an increase in power draw). Size: 11"x40"x9".

LiteGear S2 Litemat 4 Kit – Hybrid

Ultra lightweight, soft color-correct hybrid (bi-color) for daylight/tungsten with a 98+ CRI. Features flicker-free dimming and variable color temperature control. Size: 40"x21".

(Litepanels)

Litepanels Astra 6X Bi-Color LED Panel

Features: variable tungsten to daylight balance, maximum power draw of 105W, beam angle of 46°, and color range of 3200-5600K.

ASTRA ACCESSORIES:

SNAPBAG® (Astra 1x1)

SNAPGRID® – 40° (Astra 1x1)

Litepanels Gemini 1x1 RGBWW LED Soft Panel

Features: rugged construction, energy efficient power draw of 200W nominal, dimmable from 100 to 0.1% without flicker or color shift, factory presets for CCT color temperature control (in increments from 2700-10,000K), 6 additional user-definable presets, and firmware update for special effects.

GEMINI ACCESSORIES:

SNAPBAG® (Gemini 1x1)

SNAPGRID® – 40° (Gemini 1x1)

Litepanels Gemini 2x1 Bi-Color LED Soft Panel

Features: maximum power draw of 325W, dimmable from 100 to 0% without flicker or color shift, 6 factory presets for CCT color temperature control (in increments from 2700-6000K), 6 additional user-definable presets, and firmware update for lighting effects.

GEMINI ACCESSORIES:

SNAPBAG®

SNAPGRID®

(Nanlux)

Nanlux Dyno Series 1200C LED Panel

Compact, soft light solution for studio or location delivering a 1200W 30 inch square smooth illumination: 2700-20,000K CCT range; wireless and remote compatibility; CCT, HSI, RGBW, X/Y, and gel library for flexible color modes; 15 customizable effects; and dimmable from 0-100% in ultra-precise intervals of just 0.1% between 1 and 100% of output

Nanlux Evoke 1200 LED Light w/FL-35 Fresnel

1.2kW LED fixture for controlling flicker-free light comparable to a 1.8kW PAR or 2.5kW HMI fresnel, using the FL-35 Fresnel attachment to narrow the beam spread from 45° to 10°.

(Quasar Science)

Quasar Science Q-LED X Crossfade LED Lamp – 2'

Features: 25W tubes (producing 90 lumens per watt), dimmable, flicker free, 95+ CRI, aluminum built frame, and tungsten color temperature from 2000K to daylight 6000K.

QUASAR ACCESSORIES:

Modern Studio Dual Fluorescent T12 Lamp Holder w/5/8" Pin

Modern Studio Fluorescent T12 Lamp Holder w/5/8" Pin

Quasar Science Q-LED X Crossfade LED Lamp – 4'

Features: 50W tubes (producing 90 lumens per watt), dimmable, flicker free, 95+ CRI, aluminum built frame, and tungsten color temperature from 2000K to daylight 6000K.

QUASAR ACCESSORIES:

Modern Studio Dual Fluorescent T12 Lamp Holder w/5/8" Pin

Modern Studio Fluorescent T12 Lamp Holder w/5/8" Pin