

LIGHTS & LIGHTING / LED

LED

(ARRI)

ARRI L7-C LE2 LED Fresnel

Features: 25% increase boost in power, beam angle 12-50°, 2800-10K, and low electrical draw at 160W.

Includes: (1) barndoor and (1) scrim set.

ARRI SkyPanel S30-C LED Softlight

Smaller, more portable version than the S60, ideal for on-the-go applications. Outputs the equivalent of a 1000W tungsten soft light while drawing a maximum of only 240W.

Includes: (1) ARRI SkyPanel Intensifier S30, (1) light diffusion panel, (1) medium diffusion panel, (1) heavy diffusion panel, (1) rail mount adapter, (1) AC/DC power pcable, and (1) power supply.

SKYPANEL ACCESSORIES:

ARRI Chimera Shallow Lightbank – Medium (SkyPanel S30)

ARRI SkyPanel Remote

ARRI SkyPanel S60-C LED Softlight

High-powered, fully tuneable LED for fine adjustments. Outputs the equivalent of a 2000W tungsten soft light while drawing a maximum of only 450W.

Includes: (1) ARRI SkyPanel Intensifier S60, (1) light diffusion panel, (1) medium diffusion panel, (1) heavy diffusion panel, (1) rail mount adapter, (1) AC/DC power cable, and (1) power supply.

SKYPANEL ACCESSORIES:

ARRI Chimera Shallow Lightbank – Medium (SkyPanel S60)

ARRI SkyPanel Honeycomb 30° S60

ARRI SkyPanel Honeycomb 60° S60

ARRI SkyPanel Remote

(Astera LED)

Astera LED AX1 Wireless PixelTube Kit w/Charging Case

System of eight wireless, pixel controllable LED RGBW batons for variety of lighting applications.

Includes: (8) AX1 PixelTubes (3 ½"), (1) AX1 Charging Case, (8) charging cables, (8) AX1 Stands, (16) AX1 Holders, (16) AX1 Eyebolts, (16) holder cotter pins, (16) ½-20 to -16 Threaded Manfrotto Stud (Spigot), (1) transmitter case, (1) transmitter box, (1) Infra Red Remote Control, (1) micro USB cable, (1) USB adapter, (1) DMX adapter cable, and (1) AX1 single charging cable.

(ikan)

ikan ID500 12"x6" LED Light (5600K)

Features wireless remote with dimming capabilities and AC/DC 12-24V pro battery options.

Includes: (1) wireless remote and (1) set of barndoors.

(ikan) Cont. –

ikan ID1000 12"x12" LED Light (5600K)

Features: wireless remote with dimming capabilities, switchable banks, and AC/DC 12-24V pro battery options.

Includes: (1) wireless remote and (1) set of barndoors.

(Litegear)

LiteGear LiteRibbon Pro LED Kit – V1 HYBRID (3200K-6000K)

Includes: (1) pelican case; (1) set of assorted flexible (cuttable) adhesive-backed LiteRibbon(R), LiteRibbon(R) Chroma, LiteStix(TM) Pro, LitePower(TM); and (1) DTAP batter adapter.

LiteGear S2 Litemat 1 Kit – Hybrid

Ultra lightweight, soft color-correct hybrid (bi-color) for daylight/tungsten with a 95 CRI, and a widened kelvin temperature range. Size: 9.5"x19".

LiteGear S2 Litemat 2L Kit – Hybrid

Ultra lightweight, soft color-correct hybrid (bi-color) for daylight/tungsten with a 95+ CRI, and a widened kelvin temperature range (without an increase in power draw). Size: 9.5"x19".

LiteGear S2 Litemat 4 Kit – Hybrid

Ultra lightweight, soft color-correct hybrid (bi-color) for daylight/tungsten with a 98 CRI. Features flicker-free dimming and variable color temperature control. Size: 40"x21".

(Litepanels)

Litepanels 1x1 Bi-Color LED Flood

Features: variable 3200-5600K color temperature, 50° beam angle, equivalent output of a 200W HMI light (heat and flicker free), and dimmable from 100 to 0%.

Litepanels 1x1 Daylight LED Flood (5600K)

Includes: (1) 6-piece bi-color gel set and (1) gel bag.

Litepanels Astra 1x1 Bi-Color LED Panel

Features: maximum power draw of 110W, flicker-free, and color range of 3200-5600K.

Litepanels Astra 6X Bi-Color LED Panel

Features: variable tungsten to daylight balance, maximum power draw of 105W, beam angle of 46°, and color range of 3200-5600K.

Litepanels Gemini 2x1 Bi-Color LED Soft Panel

Features: maximum power draw of 325W, dimmable from 100 to 0% without flicker or color shift, 6 factory presets for CCT color temperature control (in increments from 2700-6000K), 6 additional user-definable presets, and firmware update for Lighting Effects.

GEMINI ACCESSORIES:

SNAPBAG®

SNAPGRID®

LED - CONT.

(Kino Flo)

Kino Flo Celeb 200 DMX LED

Features: flicker-free, color temperature of 2700-5500K, LED equivalent to 750W tungsten, and dimming/programmable presets from 2700K to 5500K.

Kino Flo Celeb 401 DMX LED

Features: LED equivalent to 2000W tungsten soft light, color temperature of 2700-6500K, and flicker-free with silent operation.

(Quasar Science)

Quasar Science Q-LED X Crossfade LED Lamp – 2'

Features: 25W tubes (producing 90 lumens per watt), dimmable, flicker free, 95+ CRI, aluminum built frame, and tungsten color temperature from 2000K to daylight 6000K.

QUASAR ACCESSORIES:

Modern Studio Dual Fluorescent T12 Lamp Holder w/5/8" Pin
Modern Studio Fluorescent T12 Lamp Holder w/5/8" Pin

Quasar Science Q-LED X Crossfade LED Lamp – 4'

Features: 50W tubes (producing 90 lumens per watt), dimmable, flicker free, 95+ CRI, aluminum built frame, and tungsten color temperature from 2000K to daylight 6000K.

QUASAR ACCESSORIES:

Modern Studio Dual Fluorescent T12 Lamp Holder w/5/8" Pin
Modern Studio Fluorescent T12 Lamp Holder w/5/8" Pin